



DC INDUCTIVE PROXIMITY SENSORS

[illegible]

3 ϕ 3x0.15
Approx.38 g


[illegible]

Approx.38 g



CE

HG-A2NO-M12E-1	1	HG-B4NO-M12E-1
HG-A2NC-M12E-1	2	HG-B4NC-M12E-1
HG-A2PO-M12E-1	3	HG-B4PO-M12E-1
HG-A2PC-M12E-1	4	HG-B4PC-M12E-1
HG-A2PS-M12E-1	5	HG-B4PS-M12E-1
HG-A2NS-M12E-1	6	HG-B4NS-M12E-1
HG-A2DO-M12E-1	7	HG-B4DO-M12E-1
HG-A2DC-M12E-1	8	HG-B4DC-M12E-1
	1	
	2	
	3	
	4	
	1	
	2	
	3	
	4	
	5	
	6	



4ϕ 3x0.15 or 4ϕ 4x0.15	
Approx.67 g	Approx.65 g

DC INDUCTIVE PROXIMITY SENSORS

Diameter
● Shielded ○ Non-shielded
Switching Distance Sn: mm
Housing Material
● With LED ○ Without LED

Picture

Operating Voltage
Ripple
No Load Current
Max. Load Current
Leakage Current
Voltage Drop
Switching Frequency
Response Time
Switching Hysteresis
Repeat Accuracy
Protection Category
Operating Temperature
Temperature Drift
Short Circuit Protection
Overload Trip Point
Material Active Face

DC 3 wire 10-30V NPN N.O.
DC 3 wire 10-30V NPN N.C.
DC 3 wire 10-30V PNP N.O.
DC 3 wire 10-30V PNP N.C.
DC 4 wire 10-30V Changeover PNP (N.O. & N.C.)
DC 4 wire 10-30V Changeover NPN (N.O. & N.C.)
DC 2 wire 10-60V N.O. *
DC 2 wire 10-60V N.C. *
DC 3 wire 10-55V NPN N.O.
DC 3 wire 10-55V NPN N.C.
DC 3 wire 10-55V PNP N.O.
DC 3 wire 10-55V PNP N.C.
DC 3 wire 5-36V NPN N.O.
DC 3 wire 5-36V NPN N.C.
DC 3 wire 5-36V PNP N.O.
DC 3 wire 5-36V PNP N.C.
DC 4 wire 5-36V Changeover PNP (N.O. & N.C.)
DC 4 wire 5-36V Changeover NPN (N.O. & N.C.)

Dimensions (unit: mm)


Cable 2M (PVC)
Weight

M12	
●	○
2 mm	4 mm
Nickel plated brass	
●	



10-30VDC / 5-36VDC / 10-55VDC / 10-60VDC
<10%
<10mA
200mA
<0.01mA
<1.5V
2KHZ 1KHZ
0.1ms/0.1ms 0.2ms/0.2ms
<15%(Sr)
<1.0%(Sr)
IP67
-25°C - +70°C
<10%(Sr)
YES
220mA
POM PBT

HG-A2NO-M12E-2	1	HG-B4NO-M12E-2
HG-A2NC-M12E-2	2	HG-B4NC-M12E-2
HG-A2PO-M12E-2	3	HG-B4PO-M12E-2
HG-A2PC-M12E-2	4	HG-B4PC-M12E-2
HG-A2DO-M12E-2	7	HG-B4DO-M12E-2
HG-A2DC-M12E-2	8	HG-B4DC-M12E-2
	1	
	2	
	3	
	4	
	1	
	2	
	3	
	4	




4 φ 3x0.15
Approx.62 g Approx.60 g

M12	
●	○
2 mm	4 mm
Nickel plated brass	
●	



10-30VDC / 5-36VDC / 10-55VDC / 10-60VDC
<10%
<10mA
200mA
<0.01mA
<1.5V
2KHZ 1KHZ
0.1ms/0.1ms 0.2ms/0.2ms
<15%(Sr)
<1.0%(Sr)
IP67
-25°C - +70°C
<10%(Sr)
YES
220mA
POM PBT

HG-A2NO-M12F2-1	1	HG-B4NO-M12F2-1
HG-A2NC-M12F2-1	2	HG-B4NC-M12F2-1
HG-A2PO-M12F2-1	3	HG-B4PO-M12F2-1
HG-A2PC-M12F2-1	4	HG-B4PC-M12F2-1
HG-A2PS-M12F2-1	5	HG-B4PS-M12F2-1
HG-A2NS-M12F2-1	6	HG-B4NS-M12F2-1
HG-A2DO-M12F2-1	7	HG-B4DO-M12F2-1
HG-A2DC-M12F2-1	8	HG-B4DC-M12F2-1
	1	
	2	
	3	
	4	
	1	
	2	
	3	
	4	
	5	
	6	




Approx.31 g Approx.30 g

DC INDUCTIVE PROXIMITY SENSORS




HG-A2NO-M12F2-2	1	HG-B4NO-M12F2-2
HG-A2NC-M12F2-2	2	HG-B4NC-M12F2-2
HG-A2PO-M12F2-2	3	HG-B4PO-M12F2-2
HG-A2PC-M12F2-2	4	HG-B4PC-M12F2-2
HG-A2DO-M12F2-2	7	HG-B4DO-M12F2-2
HG-A2DC-M12F2-2	8	HG-B4DC-M12F2-2
	1	
	2	
	3	
	4	
	1	
	2	
	3	
	4	



Two stainless steel cable glands are shown, each with a cable passing through it. The glands have a hexagonal base and a cylindrical body. A CE mark is visible in the bottom right corner of the image.

HG-A4NO-M12E-1	1	HG-B8NO-M12E-1
HG-A4NC-M12E-1	2	HG-B8NC-M12E-1
HG-A4PO-M12E-1	3	HG-B8PO-M12E-1
HG-A4PC-M12E-1	4	HG-B8PC-M12E-1
HG-A4PS-M12E-1	5	HG-B8PS-M12E-1
HG-A4NS-M12E-1	6	HG-B8NS-M12E-1
HG-A4DO-M12E-1	7	HG-B8DO-M12E-1
HG-A4DC-M12E-1	8	HG-B8DC-M12E-1
	1	
	2	
	3	
	4	
	1	
	2	
	3	
	4	
	5	
	6	

[illegible]